JV400LX Series

Mimaki[™]



Eco-friendly latex inkjet printer series

The JV400LX Series uses eco friendly, water-based latex inks that are fast-drying for immediate handling or secondary processing. This cooler-running model is more energy efficient yet still delivers breathtaking print quality. It features ecologically friendly orange and green ink – plus the world's first white latex ink – to produce a wide range of applications.

- Eco friendly, water-based latex inks
- Green + orange inks expand the color gamut
- World's first white latex ink enables printing on metallic or transparent media
 - > Mimaki Circulation Technology helps keep white pigments from settling
- Variable dot printing produces smooth gradations
- Three-way intelligent heater
- Nozzle Check Unit and Nozzle Recovery System

For best results, always use Mimaki original inks



Printhead	On-demand piezo.	two in-line print heads per color	
Print resolution	600 dpi, 900 dpi, 1,200 dpi		
Print speed (4 color mode)	JV400-130LX	183 SqFt/Hr (17 SqM/Hr)	
	JV400-160LX	196 SqFt/Hr (18.2 SqM/Hr)	
Maximum print width	JV400-130LX	53.5 in (1,361 mm)	
	JV400-160LX	63.3 in (1,610 mm)	
Maximum media width	JV400-130LX	53.9 in (1,371 mm)	
	JV400-160LX	63.7 in (1,620 mm)	3
Ink Type/Color	LX101 latex ink: C, M, Y, K, Gr, Or, W		
Ink Package size	600ml ink pack for C, M, Y, K, Gr, Or		7
	220ml cartridge only for White ink		
Rolled media weight	55 lbs (25 kg)		
Certifications	VCCI class A, FCC class A, UL 60950-1		
	CE Marking (EMC, Low voltage, and Machinery directive) CB		
Interface	USB 2.0		
Power supply	Single-phase (AC100 - 120V / AC200 - 240V) x2		
Power consumption	AC100V: 1.44kW x2 or less / AC200V: 1.8kW x2 or less		
Operational environment	Temperature: 59 – 86 °F (15 – 30 °C)		
	Humidity: 35 – 65% Rh (Non condensing)		
Dimensions (W \times D \times H)	JV400-130LX	104 x 34 x 56 in (2,630 x 850 x 1,430 mm)	
	JV400-160LX	113 x 34 x 56 in (2,880 x 850 x 1,430 mm)	
Weight	JV400-130LX	476 lbs (216 kg)	
	JV400-160LX	509 lbs (231 kg)	

Please visit us at: www.mimakiusa.com

Mimaki USA, Inc. 150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2016, Mimaki USA, Inc.

Rev. 11/15/16