

# TS500P-3200



super wide format dye sublimation inkjet printer

130"

## Dedicated transfer printer for oversized textile applications

The TS500P-3200 printer is a dedicated transfer model developed for production transfer runs to create extra-wide textile applications such as soft signage, home furnishing and hospitality fabrics. Designed to print onto the thinnest of transfer paper, it includes a high gap printhead that is unaffected by cockling when using thin media, while maintaining extremely high quality output.

- Includes technologies for printing onto thin transfer media without cockling interference
- 12 printheads in a staggered configuration
- Productivity of up to 1,937 SqFt/hr (180 SqM/hr)
- Auto Media Feeder for stable media feed and take-up
- Four independent post heaters prevent media cockling
- Sb310 dye sublimation inks in four or six color configurations
- Two liter ink bottles for all colors, with external ink feeding system
- Uninterrupted Ink Supply System
- Standard degassing module helps prevent nozzle failures
- Variable dot printing for exceptional image quality and MAPS4 for smooth images
- Nozzle Check Unit and Nozzle Recovery System
- Ethernet connectivity and email notification

*For best results, always use Mimaki original inks*

# Mimaki™ TS500P-3200

<b>Printhead</b>	On-demand piezo, 12 print heads in a staggered configuration	
<b>Print resolution</b>	360 dpi, 540 dpi, 720 dpi, 1,080 dpi	
<b>Print speed (4 color mode)</b>	Draft (2-pass)	1,937 SqFt (180 SqM) / Hr
	Standard (6-pass)	753 SqFt (70 SqM) / Hr
	High Quality (9-pass)	538 SqFt (50 SqM) / Hr
<b>Maximum print width</b>	129.5 in (3,290 mm)	
<b>Maximum media width</b>	129.9 in (3,300 mm)	
<b>Ink Type/Color</b>	Sb310 dye sublimation: BI, M, Y, K, Lbl, Lm	
<b>Ink Package size</b>	Ink packaged in 2 liter bottles, poured into 3 liter external ink tanks	
<b>Media thickness</b>	0.2 mm or less	
<b>Rolled media weight</b>	286.6 lbs (130 kg) or less	
<b>Certifications</b>	VCCI class A, FCC class A, ETL UL 60950-1	
	CE Marking (EMC, Low voltage, Machinery directive, and RoHS)	
	CB report, REACH, UL	
<b>Interface</b>	Ethernet 1000BASE-T, USB 2.0	
<b>Power supply</b>	Single-phase (AC200 – 240V), 50/60Hz, 29A	
<b>Power consumption</b>	6.96kW or less	
<b>Operational environment</b>	Temperature: 68 – 86 °F (20 – 30 °C)	
	Humidity: 35 – 65% Rh (Non condensing)	
<b>Dimensions (W x D x H)</b>	221.2 x 70.8 x 71.6 in (5,620 x 1,800 x 1,820 mm)	
<b>Weight</b>	3,197 lbs (1,450 kg)	

super wide format dye sublimation inkjet printer

130"

Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Mimaki USA, Inc.  
150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2016, Mimaki USA, Inc.

Rev. 08/26/16