

TX300P-1800B



wide format direct textile inkjet printer

75"

Direct-to-fabric printer with belt drive

The TX300P-1800B printer was designed specifically for direct-to-fabric printing, and incorporates a belt drive for sheet or elastic fabrics. It includes new print heads with a high gap setting that enables printing on thick or thin textiles, plus woven or raised fiber surfaces, while maintaining accurate ink droplet placement.

- High head gap setting for direct printing onto thick, thin, woven or raised fiber textiles
- Belt drive ensures fabric stability without pulling
 - > Suitable for stretchy and thin fabrics
- Multiple ink types for printing to a wide range of fabrics, for a variety of applications
 - > Ink types available – textile pigment, dye sublimation, disperse dye, reactive dye, acid dye
- Variable dot printing for exceptional image quality and MAPS4 for smooth images
- Nozzle Check Unit and Nozzle Recovery System
- Ethernet and email notification
- MBIS3 two-liter bulk ink system
- Dual Ink (Hybrid) delivery system
 - > One printer can be loaded with both dye sublimation & textile pigment ink*

* Release TBD

For best results, always use Mimaki original inks.

Mimaki™ TX300P-1800B

Printhead	On-demand piezo, four print heads in an in-line configuration
Print resolution	360, 540, 720, 1,080, 1,440 dpi (supported resolution depends on ink type)
Print speed (4 color mode)	Draft (2-pass) 732 SqFt (68 SqM) / Hr
	Standard (6-pass) 398 SqFt (37 SqM) / Hr
	High Quality (12-pass) 151 SqFt (10 SqM) / Hr
Maximum print width	74.02 in (1,880 mm) on a 2- or 3-inch core
	72.8 in (1,850 mm) on a 1-inch core (requires optional 1-inch adapter)
Maximum media width	75.8 in (1,900 mm) on a 2- or 3-inch core
	72.8 in (1,850 mm) on a 1-inch core (requires optional 1-inch adapter)
Ink Type/Color	Sb420 dye sublimation ink: Bl, M, Y, K, Lbl, Lm
	Dd400 disperse dye: C, M, Y, K, R, Grey (Lk), Violet, Pink*
	RC400 reactive dye: C, M, Y, K, Bl, R, Or, Lk
	AC400 acid dye: C, M, Y, K, Bl, R, Or, Lk
	TP400 textile pigment: C, M, Y, K (Bl, R, Lk*)
	<i>*future availability – check with your Mimaki representative</i>
Ink Package Size	2L ink pack
Media Thickness	1.0 mm max
Rolled Media Weight	88.2 lbs. (40 kg) on a 2- or 3-inch core
	75 lbs. (34 kg) on a 1-inch core
	<i>Maximum weight after printing</i>
Certifications	VCCI Class A / FCC Class A / UL60950-1ETL
	CE Marking (EMC, Low voltage, Machinery) CB report / RoHS / REACH / RCM
Interface	For print data: Ethernet 1000BASE-T / USB 2.0 Hi-speed
	For e-mail: Ethernet 10BASE-T / 100BASE-TX / 1000BASE-T
Power Supply	Single phase (AC100~120V/200~240V ±10%)×1 50/60Hz±1Hz
Power Consumption	(AC100V) 1,440W, (AC200V) 1,920W
Operational Environment	Temp: 68° - 86° F (20°-30° C)
	35-65% RH (non-condensing)
Dimensions (W x D x H)	125.3 x 75.2 x 72.5 in (3183 x 1912 x 1844 mm), printer only
Weight	1,382 lbs. (627 Kg), printer only

wide format direct textile inkjet printer

75"

Please visit us at: www.mimakiusa.com

Mimaki USA, Inc.
150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2017, Mimaki USA, Inc.

Rev. 04/04/17